

MIRROR

MIX 551 ONE-WAY AND SECURITY MIRROR

INDOOR INSTALLATION



Reinforces the glazing

ONE-WAY AND SECURITY MIRROR

DESCRIPTION

A large number of special-purpose premises require the highest level of confidentiality and security and yet, depending on their location, are exposed to all types of visual and physical intrusions.

With its reinforced thickness, MIX 551 meets all the protection requirements of glazed buildings in terms of privacy and security.



Durability: 12 to 15 years for a vertical application in Central Europe.



Use: For clear glass and double glazing smaller than 1.20 m².



Maintenance : after 30 days with a usual cleaning solution (non abrasive, without ammonia...). Cleaning products that could scratch are not recommended.



Storage: 2 years from delivery. This film must be stored away from excessive humidity and sunlight, at a temperature below 38°C.

In order to meet high standards, we recommend that you do not mix films from different productions

INFORMATION

MATERIAL :PET
ADHESIVE :Acrylic polymer 13 gr/m²
LINER :Siliconized PET 23 microns
THICKNESS :115 microns
COLOR :Silver
APPLICATION SIDE :Internal
TRANSMISSION UVA :1%
APPLICATION T° :min, + 5°C
STANDARDS :EUROCLASSES
FIRE RANTING : B-s1,d0
GUARANTEE :10 Years inside*

* For glazing not exposed to the sun

DIMENSIONS

By roll :



1,52 x

10 m
30 m

Application
Note



Video of the
installation



Method of application

The surface to be bonded must be free of dust, grease or any other contaminant. Some materials such as polycarbonate can cause bubbling problems. A compatibility test is therefore recommended. Possibility to install on plexiglass and polycarbonate.

Production monitoring and standards

In order to constantly improve our productions, we may have to modify without notice the colors and manufacturing processes. We recommend to our users, before applying our films, to make sure that they are exactly suitable for the intended use and to comply with the standards in force.